



Kelvin Led Base

Designed by Antonio Citterio, 2009



8W - 285lm - 3000K

Adjustable table lamp providing direct lighting, with double pantograph arm and adjustable head. Fused aluminum alloy body. Die-cast aluminum outer head, with injection-molded methacrylate diffuser. BASE external cover in ABS. Extruded aluminum alloy square tube (12x12mm) structure, machined mechanically, so that it houses a stainless steel load-compensation spring and injection-molded acetal resin sliding blocks. 3 mm diameter wire outer tie rods. Available in white, anthracite, black or chrome finishes. The ON/OFF switch is electronic with optical mechanism located in the head. Two possibilities to choose: - PERSONAL MODE (orange switch) Dimm the light intensity you like. - GREEN MODE (green switch) Now Kelvin LED becomes Green, saving even more energy thanks to his automatic compensation of the ambience light.

581 mm

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

| EAN | 8059607004067 |
|-------------------|---------------------|
| Mounting | Table |
| Enviroment | Indoor dry location |
| Light source type | LED |
| LED type | LED Module |
| Lamp holder | LED Module |
| Power (W) | 8 |
| System flux (lm) | 285 |

Physical

| Colour | Black |
|---------------------|-------|
| Length (mm) | 100 |
| Cord length (mm) | 1800 |
| Net weight (kg) | 3.9 |
| Package volume (m3) | 0.02 |
| IP | 20 |

Download

| Mounting instructions | <u>↓</u> PDF |
|-----------------------|--------------|
| Mounting instructions | 业 PDF |
| Mounting instructions | ↓ PDF |
| Spare Parts | 业 PDF |

Photometric Files

| .DT / IES | 1 | LDT |
|-----------|---|-----|
| | | |

Technical Drawings

| 2D | ⊥ ZIP |
|----|--------------|
| 3D | <u>↓</u> ZIP |

















https://professional.flos.com/en/global/product/kelvin-led-base-f3311030/

F3311030

Schematic light drawing



Luminous flux luminaire

Photometric

| Lighting type | Direct |
|--------------------|-----------|
| Light distribution | Symmetric |
| CCT (K) | 3000 |

Electrical

| Insulation class | III |
|--------------------|---------------------------|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 100-240/24 |
| Driver | Remote included |
| Dimming type | Electronic 24V |
| Cord length (mm) | 1800 |
| Plug type | Type G, Type A, Type C |
| Batteries inside | No |
| Charging min time | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts





Kelvin led gm black body



F3322030A

Kelvin led gm black base



RF18764

Black insert for lamp base



RF3320100

Black plug assembly kit & 24V driver